

Handlampe Set IP66

Artikel Nummer / item no. 750300



Technische Daten | Technical data

PENLIGHT IP66

| | |
|---|--|
| Ausstattung features | Spot: SMD Lampe: COB |
| Leistung power | Spot: 1W Lampe level1/2: 1,5/2W |
| Lumen luminous flux | Spot: 50lm Lampe level1/2: 90/130lm |
| Farbtemperatur colour temperature | 6000K |
| Farbwiedergabe colour rendering index | ≥70Ra |
| Akku / Li-ion battery | 3,7V/1100mAh |
| Ladedauer charging time | 3 Std. |
| Leuchtdauer working duration | Spot: 6 Std. Lampe level1/2: 4/3 Std. |
| Lebensdauer life span LED | 25000 Std. |
| Schutzart protection class | IP66 |
| Abmessung measures | 192*22,5*27,5mm |
| Gewicht weight | 88g (netto) |
| Material (Gehäuse) material (housing) | ABS, PC |

Ladestation

| | |
|---|-------------------------------------|
| Netzteil power supply | AC-DC Adapter 100-240V 50/60Hz |
| Ladestrom charging current | DC 5V/2A |
| Stecker connector | Type-C |
| Abmessung measures | 110*100*73mm |
| Gewicht weight | 225g (netto) |
| Material (Gehäuse) material (housing) | ABS |

WORKLIGHT IP66

| | |
|---|--|
| Ausstattung features | Spot: SMD Lampe: COB |
| Leistung power | Spot: 1,2W Lampe level1/2: 2/3W |
| Lumen luminous flux | Spot: 90lm Lampe level1/2: 200/300lm |
| Farbtemperatur colour temperature | 6000K |
| Farbwiedergabe colour rendering index | ≥70Ra |
| Akku / Li-ion battery | 3,7V/1100mAh |
| Ladedauer charging time | 3 Std. |
| Leuchtdauer working duration | Spot: 5 Std. Lampe level1/2: 3/2 Std. |
| Lebensdauer life span LED | 25000 Std. |
| Schutzart protection class | IP66 |
| Abmessung measures | 245*43*37mm |
| Gewicht weight | 188g (netto) |
| Material (Gehäuse) material (housing) | ABS,PC,TPR |